


## I-Beams



| DIE #  | A     | B     | C     | D     | E     | F       | WT/FT |
|--------|-------|-------|-------|-------|-------|---------|-------|
| SS3724 | 1.500 | 1.500 | 0.125 | 0.125 | 0.015 | 0.015   | 0.637 |
| SS2239 | 1.700 | 1.300 | 0.080 | 0.080 | 0.020 | 0.020   | 0.397 |
| SS3732 | 2.000 | 1.000 | 0.125 | 0.100 | 0.200 | 0.015   | 0.551 |
| SS0137 | 2.032 | 3.255 | 0.250 | 0.250 | 0.063 | Full R. | 2.384 |
| SS1211 | 3.000 | 2.000 | 0.110 | 0.090 | 0.094 | 0.047   | 0.816 |
| SS2134 | 3.000 | 2.000 | 0.156 | 0.125 | 0.094 | 0.047   | 1.158 |
| SS1103 | 3.000 | 2.330 | 0.170 | 0.170 | 0.270 | 0.015   | 2.148 |
| SS2687 | 4.000 | 3.000 | 0.125 | 0.125 | 0.062 | 0.015   | 1.466 |
| SS2095 | 4.000 | 3.000 | 0.230 | 0.150 | 0.250 | 0.015   | 2.357 |
| SS2062 | 4.000 | 3.500 | 0.250 | 0.250 | 0.188 | 0.250   | 3.122 |
| SS2679 | 4.500 | 3.000 | 0.250 | 0.188 | 0.250 | 0.015   | 2.764 |
| SS2801 | 6.000 | 4.000 | 0.350 | 0.210 | 0.300 | 0.015   | 4.788 |

\* Indicates Aluminum Association Standard I-Beam

\*

\*

\*

(Not Available In Alloy 6061)